


Dissecting WPA3

#sf22us



The image shows a Wireshark capture of a WPA3 handshake. The table below summarizes the key frames:

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	136	Beacon frame, SN=0, FN=0, Flags=....., BI=100, SSID=MPA3-Network
2	0.085497	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	105	Probe Request, SN=0, FN=0, Flags=....., SSID=Wildcard (Broadcast)
3	0.085789	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	130	Probe Response, SN=0, FN=0, Flags=....., BI=100, SSID=MPA3-Network
5	3.634814	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	150	Authentication, SN=11, FN=0, Flags=.....
7	3.678653	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	150	Authentication, SN=1, FN=0, Flags=.....
9	3.679780	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	86	Authentication, SN=12, FN=0, Flags=.....
11	3.681400	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	86	Authentication, SN=2, FN=0, Flags=.....
13	3.686583	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	141	Association Request, SN=13, FN=0, Flags=....., SSID=MPA3-Network
15	3.686761	02:00:00:00:00:00	02:00:00:00:00:00	BroadCast	78	Association Response, SN=3, FN=0, Flags=.....
17	3.689229	02:00:00:00:00:00	02:00:00:00:00:00	EAPOL	175	Key (Message 1 of 4)
19	3.783343	02:00:00:00:00:00	02:00:00:00:00:00	EAPOL	181	Key (Message 2 of 4)
21	3.783713	02:00:00:00:00:00	02:00:00:00:00:00	EAPOL	241	Key (Message 3 of 4)
23	3.829218	02:00:00:00:00:00	02:00:00:00:00:00	EAPOL	153	Key (Message 4 of 4)

Megumi Takeshita
Ikeriri network service




Materials: all trace files, python codes are here

<https://www.ikeriri.ne.jp/sharkfest/03DissectingWPA3.zip>

Megumi Takeshita, packet otaku



- Founder, ikeriri network service co., ltd #sf22us
- Reseller of CACE technologies in 2008
- Worked SE/IS at BayNetwork, Nortel
- Wrote 10+ books about Wireshark
- Instruct Wireshark to JSDF and other company
- Reseller of packet capture / wireless-tools
- One of the contributors of Wireshark
- Translate Wireshark into Japanese



Session Details

We need a new security standard in the 6/6E generation of WiFi. WPA3 has an SAE (Simultaneous Authentication of Equals) authentication handshake and PMF (Protected Management Frames) mechanism. In this session, Megumi shows you WPA3 trace analysis using Wireshark. Follow the packets and understand the safe way to use the wireless network

Materials

all trace files and Wireshark profiles are here

<https://www.ikeriri.ne.jp/sharkfest/03DissectingWPA3.zip>

WPA2-PSK dissection



- Open `wpa2psk-ssid-ikeriri6-pass-wireshark.pcapng` this trace is captured and decrypted by TamoSoft CommView for WiFi in the WiFi6 environment
- It is a typical linkup process of WPA2-PSK between iphone13 (private MAC address) and ASUS AP

Time	PHY type	Channel	data E	Signal (dBm)	Noise (dBm)	data M	Data rate	Retry	Type/Subtype
1 0.000000	802.11a (OFDM)	56		-39 dBm	-93 dBm			6 Frame is not...	Authentication
2 0.001283	802.11a (OFDM)	56		-33 dBm	-93 dBm			6 Frame is not...	Authentication
3 0.002746	802.11a (OFDM)	56		-41 dBm	-93 dBm			6 Frame is not...	Association Request
4 0.005013	802.11a (OFDM)	56		-33 dBm	-93 dBm			6 Frame is not...	Association Response
5 0.008401	802.11a (OFDM)	56		-33 dBm	-93 dBm			6 Frame is not...	QoS Data
6 0.010452	802.11a (OFDM)	56		-41 dBm	-93 dBm			6 Frame is not...	QoS Data
7 0.011950	802.11a (OFDM)	56		-33 dBm	-93 dBm			6 Frame is not...	QoS Data
8 0.013064	802.11a (OFDM)	56		-41 dBm	-91 dBm			6 Frame is not...	QoS Data
9 0.072760	802.11ax (HE)	56	20	-41 dBm	-91 dBm	0xb	270.8	6 Frame is not...	QoS Data
10 0.072892	802.11ax (HE)	56	20	-41 dBm	-91 dBm	0xb	270.8	6 Frame is not...	QoS Data
11 0.073031	802.11ax (HE)	56	20	-41 dBm	-91 dBm	0xb	270.8	6 Frame is not...	QoS Data
12 0.073376	802.11ax (HE)	56	20	-41 dBm	-91 dBm	0xb	270.8	6 Frame is not...	QoS Data
13 0.073578	802.11a (OFDM)	56		-33 dBm	-91 dBm			6 Frame is not...	Data


4way handshake (common in WPA2 and WPA3)

- There are 4 way handshake after link-up process,
- Enter “eapol” in Display filter and make FlowGraph



- At first, AP sends Key(Message 1 of 4) and STA reply Key (Message 2 of 4) to exchange PTK for unicast. Then AP sends Key (Message 3 of 4), STA replies. Key (Message 4 of 4) to confirm GTK for multicast.


- The passphrase is used for PSK (Pre Shared Key)
- PMK (Pairwise Master Key) is created by 4096 round times calculation of PBKDF2 hash function, with SHA1 algorithm, using PSK and SSID
e.x. $PMK = pbkdf2_hmac('sha1', PSK, SSID, 4096)$
- Lets's start checking PMK using Wireshark
Go back to the trace, wpa2psk-ssid-ikeriri6-pass-wireshark.pcapng, and check the #5 packet, the first EAPOL message 1/4

 wpa2psk-ssid-ikeriri6-pass-wireshark.pcapng File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help


Set Decryption key in Wireshark



#sf22us




- Select “IEEE 802.11 QoS Data, Flags:F.” header, right-click and choose Protocol preference > Open IEEE802.11 wireless preferences...



- Click “Edit...” button of the Decryption keys


- We can set 5 styles of WEP and WPA decryption keys in Wireshark 3.6



Key,	stype	explanation
wep	WEP key (hex value)	for WEP encryption
wpa-pwd	Passphrase:SSID (ascii)	For WPA1-PSK, WPA2-PSK
wpa-psk	Raw PSK (hex value)	256-bit pre-shared ("raw") key https://www.wireshark.org/tools/wpa-psk.html
tk	Temporal Key (hex value)	TK is used for actual encryption key, TK is a part of PTK (Pairwise-Transient-Key)
msk	Master Session Key (hex value)	Master Session key is derived from 802.1x EAP authentication process if you use WPA1-EAP, WPA2-EAP. You can set msk from the debug information of the AP and wireless lan controller.

- Set key type as “wpa-pwd” and input key “wireshark:ikeriri6” in decryption key dialog

#sf22us



- Click “OK” to close WEP and WPA decryption Keys dialog
- “OK” again to close IEEE802.11 wireless LAN preference

Confirm your QoS Data frames are decrypted

No.	Time	PHY type	Chann	data E	Signal (dBm)	Noise (dBm)	data L	Data cr.	Rate	Type/Status	Source	Destination	Length	Info
1	0.900	802.11a (OFDM)	56	-36 dBm	-93 dBm				6	Frame 1s - Authentication	e2:da:1e:a8:92:8f	ASUSTekL	97	Authentication, SM=331, FN=0, Flags=.....
2	0.901	802.11a (OFDM)	56	-33 dBm	-93 dBm				6	Frame 1s - Authentication	A9:57:6c:c4:f5:c4	e2:da:1e:a8:92:8f	92	Authentication, SM=0, FN=0, Flags=.....
3	0.902	802.11a (OFDM)	56	-41 dBm	-93 dBm				6	Frame 1s - Association Request	e2:da:1e:a8:92:8f	ASUSTekL	237	Association Request, SM=210, FN=0, Flags=....., SSID=iterir16
4	0.905	802.11a (OFDM)	56	-33 dBm	-93 dBm				6	Frame 1s - Association Response	A9:57:6c:c4:f5:c4	e2:da:1e:a8:92:8f	238	Association Response, SM=1, FN=0, Flags=.....
5	0.908	802.11a (OFDM)	56	-33 dBm	-93 dBm				6	Frame 1s - QoS Data	A9:57:6c:c4:f5:c4	e2:da:1e:a8:92:8f	100	Key (Message 1 of 4)
6	0.910	802.11a (OFDM)	56	-31 dBm	-93 dBm				6	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	ASUSTekL	107	Key (Message 2 of 4)
7	0.911	802.11a (OFDM)	56	-33 dBm	-93 dBm				6	Frame 1s - QoS Data	A9:57:6c:c4:f5:c4	e2:da:1e:a8:92:8f	237	Key (Message 3 of 4)
8	0.911	802.11a (OFDM)	56	-41 dBm	-91 dBm				6	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	ASUSTekL	100	Key (Message 4 of 4)
9	0.972	802.11ax (HE)	56	29	-41 dBm	-91 dBm	0xb	270.8	8	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	IPW6mas	170	QoS Data, SM=0, FN=0, Flags=0b.....T
10	0.972	802.11ax (HE)	56	29	-41 dBm	-91 dBm	0xb	270.8	8	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	ASUSTekL	126	QoS Data, SM=1, FN=0, Flags=0b.....T
11	0.973	802.11ax (HE)	56	29	-41 dBm	-91 dBm	0xb	270.8	8	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	Broadcast	426	QoS Data, SM=2, FN=0, Flags=0b.....T
12	0.973	802.11ax (HE)	56	29	-41 dBm	-91 dBm	0xb	270.8	8	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	IPW6mas	166	QoS Data, SM=3, FN=0, Flags=0b.....T
13	0.973	802.11a (OFDM)	56	-33 dBm	-91 dBm				6	Frame 1s - Data	::	FF02::1::	130	Neighbor Solicitation for fe80::1a42:c009:0201:27fa



No.	Time	PHY type	Chann	data E	Signal (dBm)	Noise (dBm)	data L	Data cr.	Rate	Type/Status	Source	Destination	Length	Info
1	0.900	802.11a (OFDM)	56	-36 dBm	-93 dBm				6	Frame 1s - Authentication	e2:da:1e:a8:92:8f	ASUSTekL	97	Authentication, SM=331, FN=0, Flags=.....
2	0.901	802.11a (OFDM)	56	-33 dBm	-93 dBm				6	Frame 1s - Authentication	A9:57:6c:c4:f5:c4	e2:da:1e:a8:92:8f	92	Authentication, SM=0, FN=0, Flags=.....
3	0.902	802.11a (OFDM)	56	-41 dBm	-93 dBm				6	Frame 1s - Association Request	e2:da:1e:a8:92:8f	ASUSTekL	237	Association Request, SM=210, FN=0, Flags=....., SSID=iterir16
4	0.905	802.11a (OFDM)	56	-33 dBm	-93 dBm				6	Frame 1s - Association Response	A9:57:6c:c4:f5:c4	e2:da:1e:a8:92:8f	238	Association Response, SM=1, FN=0, Flags=.....
5	0.908	802.11a (OFDM)	56	-33 dBm	-93 dBm				6	Frame 1s - QoS Data	A9:57:6c:c4:f5:c4	e2:da:1e:a8:92:8f	100	Key (Message 1 of 4)
6	0.910	802.11a (OFDM)	56	-31 dBm	-93 dBm				6	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	ASUSTekL	107	Key (Message 2 of 4)
7	0.911	802.11a (OFDM)	56	-33 dBm	-93 dBm				6	Frame 1s - QoS Data	A9:57:6c:c4:f5:c4	e2:da:1e:a8:92:8f	237	Key (Message 3 of 4)
8	0.911	802.11a (OFDM)	56	-41 dBm	-91 dBm				6	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	ASUSTekL	100	Key (Message 4 of 4)
9	0.972	802.11ax (HE)	56	29	-41 dBm	-91 dBm	0xb	270.8	8	Frame 1s - QoS Data	::	FF02::1::	170	Neighbor Solicitation for fe80::1a42:c009:0201:27fa
10	0.972	802.11ax (HE)	56	29	-41 dBm	-91 dBm	0xb	270.8	8	Frame 1s - QoS Data	e2:da:1e:a8:92:8f	ASUSTekL	126	QoS Data, SM=1, FN=0, Flags=0b.....T
11	0.973	802.11ax (HE)	56	29	-41 dBm	-91 dBm	0xb	270.8	8	Frame 1s - QoS Data	0.0.0.0	255.255.255.255	426	NDP Request - Transaction ID 0xac9e7500
12	0.973	802.11ax (HE)	56	29	-41 dBm	-91 dBm	0xb	270.8	8	Frame 1s - QoS Data	fe80::1a42:c009:0201:27fa	FF02::1	146	Router Solicitation
13	0.973	802.11a (OFDM)	56	-33 dBm	-91 dBm				6	Frame 1s - Data	::	FF02::1::	136	Neighbor Solicitation for fe80::1a42:c009:0201:27fa

- Choose first QoS Data frame #9 and open IEEE802.11 QoS Data Header > CCMP (Counter mode with Cipher-block chaining Message authentication code Protocol) parameters

TK(wlan.analysis.tk) and PMK(wlan.analysis.pmk)



#sf22us

CCMP parameters

CCMP Ext. Initialization Vector: 0x000000000002

Key Index: 0

[TK: 4c102fd43613c535404d0777088a6503]

[PMK: 31bb75a609a424aac01e9929b39458e87ea45b0f30204ff5642bf3067a6fd31f]

- Wireshark decrypt 4way handshake and add generated fields, TK(Temporal Key), actual AES key of the communication and PMK(Pairwise Master Key) 32 bytes(256bit), 4096 round times calculation of PBKDF2 function with SHA1 algorithm, using PSK and SSID
- We can also test this calculation by Python

```
from hashlib import pbkdf2_hmac
pwd="wireshark"
ssid="ikeriri6"
pmk = pbkdf2_hmac('sha1', pwd.encode('ascii'), ssid.encode('ascii'), 4096, 32)
print(pmk.hex())
```

Check PMK generation by VisualStudio Code



#sf22us

```
psk.py > ...
1 from hashlib import pbkdf2_hmac
2 pwd="wireshark"
3 ssid="ikeriri6"
4 pmk = pbkdf2_hmac('sha1', pwd.encode('ascii'), ssid.encode('ascii'), 4096, 32)
5 print(pmk.hex())
```

- Run pmk.py to check the PMK from the output with Wireshark [PMK:] field, it is the same value

```
gMPA3> & C:/Users/TakeshitaMegumi/AppData/Local/Microsoft/WindowsApps/python3.9.exe "C:/Users/TakeshitaMegumi/OneDrive - いけりりネットワークサービス株式会社/Sharkfest/Sharkfest2022/03DissectingWPA3/psk.py"
31bb75a609a424aac01e9929b39458e87ea45b0f30204ff5642bf3067a6fd31f
```

[PMK: 31bb75a609a424aac01e9929b39458e87ea45b0f30204ff5642bf3067a6fd31f]

- Station (iPhone13) and AP (ASUS) share this information, but never send it to the network.

Let's start dissecting 4way handshake



#sf22us

- ASUS(AP) and iPhone13(STA) know the same PMK

[PMK: 31bb75a609a424aac01e9929b39458e87ea45b0f30204ff5642bf3067a6fd31f]

- Exchange and Confirm PTK in Messages 1,2
- Exchange and Confirm GTK in Messages 3,4

Packet #5 Key(Message 1 of 4) AP->STA



#sf22us

4	0.005...	802.11a (OFDM)	56	-33 dBm	-93 dBm	6 Fram
5	0.008...	802.11a (OFDM)	56	-33 dBm	-93 dBm	6 Fram
6	0.010...	802.11a (OFDM)	56	-41 dBm	-93 dBm	6 Fram
7	0.011...	802.11a (OFDM)	56	-33 dBm	-93 dBm	6 Fram
8	0.013...	802.11a (OFDM)	56	-41 dBm	-91 dBm	6 Fram

```

> Frame 5: 165 bytes on wire (1320 bits), 165 bytes captured (1320 bits) on interface
> Radiotap Header v0, Length 32
> 802.11 radio information
> IEEE 802.11 QoS Data, Flags: .....F.
> Logical-Link Control
< 802.1X Authentication
  Version: 802.1X-2004 (2)
  Type: Key (3)
  Length: 95
  Key Descriptor Type: EAPOL RSN Key (2)
  [Message number: 1]
  > Key Information: 0x008a
  Key Length: 16
  Replay Counter: 1
  WPA Key Nonce: 812e47f04e25fa494c7d44b2f7b016e0e3f24865fd134f4998a8f5d0d68bc0
  Key IV: 00000000000000000000000000000000
  WPA Key RSC: 0000000000000000
  WPA Key ID: 0000000000000000
  WPA Key MIC: 00000000000000000000000000000000
  WPA Key Data Length: 8
  
```

- AP creates and sends Nonce (ANonce), 32bytes random value.
- Message1 packet also contains AP's MAC Address.

PTK creation from STA(iPhone) side (1of4)



- STA starts to create PTK (Pairwise Transient Key) after STA received EAPOL Message 1of4 (Packet 5)
- STA creates its own Nonce(Snonce), 32bytes random
- PTK is created from ANonce, Snonce, AP MAC address and STA mac address

PTK = PRF-512(PMK, “Pairwise key expansion”,
 Min(AP MAC, STA MAC) || Max(AP MAC, STA MAC) ||
 Min(ANonce, SNonce) || Max(ANonce, SNonce))

*PRF(Pseudo-Random Function) is SHA1 hash value from input parameter, PMK, “Pairwise key expansion” and Min(AP MAC, STA MAC) || Max(AP MAC, STA MAC) || Min(ANonce, SNonce) || Max(ANonce, SNonce))

PTK is a big key ring consists of many WPA2/WPA3 keys

PMK (Primary Master Key) 256bits

**Anonce
32bytes random**

**SNonce
32 bytes random**

**AMAC
AP's MAC address**

**SMAC
STA's MAC address**

PTK = PRF-512(PMK, "Pairwise key expansion", Min(AP MAC, STA MAC) || Max(AP MAC, STA MAC) || Min(ANonce, SNonce) || Max(ANonce, SNonce))

PTK (Pairwise Transient Key) 512bit

EAPOL KEK (Key Encryption Key) 128bits

EAPOL KCK (Key Confirmation Key) 128bits

Temporal Key 128bits for actual communication AES encryption/decryption key

Receive MIC Key (MIC Secret) 64bits for receiving packet Message Integrity Code

Transmit MIC Key (MIC Secret) 64bits for sending packet Message Integrity Code

Packet #6 Key(Message 2 of 4) STA->AP

Time	Source	Destination	Length	Signal	SNR	Frame
4.0.005	802.11a (OFDM)		56	-33 dBm	-93 dBm	6 Frame
5.0.008	802.11a (OFDM)		56	-33 dBm	-93 dBm	6 Frame
6.0.010	802.11a (OFDM)		56	-41 dBm	-93 dBm	6 Frame
7.0.011	802.11a (OFDM)		56	-33 dBm	-93 dBm	6 Frame
8.0.013	802.11a (OFDM)		56	-41 dBm	-91 dBm	6 Frame

```

> Frame 6: 187 bytes on wire (1496 bits), 187 bytes captured (1496 bits) on interface
> Radiotap Header v0, Length 32
> 802.11 radio information
> IEEE 802.11 QoS Data, Flags: .....T
> Logical-Link Control
< 802.1X Authentication
  Version: 802.1X-2004 (2)
  Type: Key (3)
  Length: 117
  Key Descriptor Type: EAPOL RSN Key (2)
  [Message number: 2]
  > Key Information: 8x010a
  Key Length: 16
  Replay Counter: 1
  NPA Key Nonce: fcf94398b971a1f20572495509733ff0000:93b142e86c9348ce23f3c287ff8b
  Key IV: 00000000000000000000000000000000
  NPA Key RSC: 0000000000000000
  NPA Key ID: 0000000000000000
  NPA Key MIC: d5aa6adf088791d7cd37b8966f8a0930
  NPA Key Data Length: 22
  > NPA Key Data: 30140100000fac040100000fac040100000fac028c00
  
```

- STA creates and sends Nonce (SNonce), 32bytes random value. #122us
- STA calculate and add WPA Key MIC
- Message2 packet also contains STA's MAC Address

STA created SNonce and Add MIC Key Data



#sf22us

- Receiving 1 of 4 Messages, STA creates PTK
- STA sets SNonce, 32 bytes random value
- STA also adds 16 bytes WPA Key MIC field, calculated SHA1 HMAC from all of the 802.1x fields


```
WPA Key MIC: d5aa6adf088791d7cd37b8866f8a0930
```

- WPA Key MIC means the confirmation that created PTK is the same with STA and AP
(Receiving 2 of 4 Message, AP also creates PTK and check the WPA Key MIC is correct)

PTK creation from AP(ASUS) side

- AP starts to create PTK (Pairwise Transcient Key) after EAPOL Message 2of4 (Packet 6)
- PTK is created from ANonce, Snonce, AP MAC address and STA mac address
$$\text{PTK} = \text{PRF-512}(\text{PMK}, \text{“Pairwise key expansion”}, \text{Min}(\text{AP MAC}, \text{STA MAC}) \parallel \text{Max}(\text{AP MAC}, \text{STA MAC}) \parallel \text{Min}(\text{ANonce}, \text{SNonce}) \parallel \text{Max}(\text{ANonce}, \text{SNonce}))$$
- AP checks the WPA Key MIC field to calculate SHA1HMAC from all of the 802.1x fields with the MIC field set to all zeros.
- If the calculated MIC is the same with the Message2of4, STA and AP shared the same PTK.

Check Actual MIC with Calculated MIC



```

802.1X Authentication
  Version: 802.1X-2004 (2)
  Type: Key (3)
  Length: 117
  Key Descriptor Type: EAPOL RSN Key (2)
  [Message number: 2]
  Key Information: 0x010a
  Key Length: 16
  Replay Counter: 1
  WPA Key Nonce: fcf94398b971a1f20572495509733ff000c93b142e86c9348ce23f3c287ff8b
  Key IV: 00000000000000000000000000000000
  WPA Key RSC: 0000000000000000
  WPA Key ID: 0000000000000000
  WPA Key MIC: d5aa6adf008791d7cd37b0866f8a0930
  WPA Key Data Length: 22
  WPA Key Data: 3014010000fac040100000fac040100000fac028c00
  
```

If calculated MIC is not the same with WPA Key MIC value of Message 2of4 (Packet6),



It usually means passphrase is not the same.

#sf22us

- Open notmatchmic.pcapng and set display filter as “wlan.addr_resolved contains Nintendo”

No.	Time	Signal [dBm]	Source	Destination	Type/Subtype	Data rate (Mb/s)	Protoc
1	0.000000	-51 dBm	Modacom_a8:55:d8	Nintendo_35:63:78	Probe Response	802	
2	0.000311	-62 dBm		Modacom_a8:55:d...	Acknowledgement	802	
3	0.010279	-50 dBm	Modacom_a8:55:d8	Broadcast	Beacon frame	802	
4	0.084443	-53 dBm	Modacom_a8:55:d8	Nintendo_35:63:78	Probe Response	802	

- This trace tested passphrase mismatch between Modacom AP and Nintendo STA.
- We can find the iteration of Message1, Message2 because AP's calculated MIC is not the same as Message 2 WPA Key MIC.

```

Modacom_a8:55:d8 Nintendo_35:63:78 QoS Data EAPOL 169 Key (Message 1 of 4)
Nintendo_35:63:78 Modacom_a8:55:d8 QoS Data EAPOL 191 Key (Message 2 of 4)
Modacom_a8:55:d8 Nintendo_35:63:78 QoS Data EAPOL 169 Key (Message 1 of 4)
Nintendo_35:63:78 Modacom_a8:55:d8 QoS Data EAPOL 191 Key (Message 2 of 4)
Modacom_a8:55:d8 Nintendo_35:63:78 QoS Data EAPOL 169 Key (Message 1 of 4)
Nintendo_35:63:78 Modacom_a8:55:d8 QoS Data EAPOL 191 Key (Message 2 of 4)
Modacom_a8:55:d8 Nintendo_35:63:78 QoS Data EAPOL 169 Key (Message 1 of 4)
Nintendo_35:63:78 Modacom_a8:55:d8 QoS Data EAPOL 191 Key (Message 2 of 4)
Modacom_a8:55:d8 Nintendo_35:63:78 Disasso... 802.11 62 Disassociate, SN=2, FN=6
  
```

PTK exchange Demonstration



#sf22us

- I referred and created the WPA2 implementation Python code from Nicholas smith
<https://nicholastsmith.wordpress.com/2016/11/15/wpa2-key-derivation-with-anaconda-python/>
- It is not perfect, not actual, but a Pseudo concept, I set parameters from the trace file.
wpa2psk-ssid-ikeriri6-pass-wireshark.pcapng
- Open ptk.py using VSCode.

Open ptk.py (I referred and created the code from Nicholas smith)



<https://nicholastsmith.wordpress.com/2016/11/15/wpa2-key-derivation-with-anaconda-python/>

#sf22us

```

ptk.py > ...
1 # Ikerpirl referred and changed the code from nicholastsmith
2 # https://nicholastsmith.wordpress.com/2016/11/15/wpa2-key-derivation-
3
4 import hmac
5 from binascii import a2b_hex, b2a_hex
6 from hashlib import pbkdf2_hmac, sha1, md5
7 import binascii
8
9 #Pseudo-random function for generation of
10 #the pairwise transient key (PTK)
11 #key:      The PTK
12 #A:       b"Pairwise key expansion"
13 #B:       The apMac, cliMac, aNonce, and sNonce concatenated
14 #         like mac1 mac2 nonce1 nonce2
15 #         such that mac1 < mac2 and nonce1 < nonce2
16 #return:   The ptk
17 def PRF(key, A, B):
18     #Number of bytes in the PTK
19     nByte = 64
20     i = 0
21     R = b''
22     #Each iteration produces 160-bit value and 512 bits are required
23     while(i <= ((nByte * 8 + 159) / 160)):
24         hmacsha1 = hmac.new(key, A + chr(0x00).encode() + B + chr(i), e
25             R = R + hmacsha1.digest()
26         i += 1
27     return R[:nByte]

```

```

20 #Make parameters for the generation of the PTK
21 #aNonce:   the nonce from the 4-way handshake
22 #sNonce:   the nonce from the 4-way handshake
23 #apMac:    the MAC address of the access point
24 #cliMac:   the MAC address of the client
25 #return:   (A, B) where A and B are parameters
26 #         for the generation of the PTK
27
28 def MakeAP(aNonce, sNonce, apMac, cliMac):
29     A = b"Pairwise key expansion"
30     B = min(apMac, cliMac) + max(apMac, cliMac) + min(aNonce, sNonce)
31     return (A, B)
32
33 #Create the 1st message integrity check for a WPA 4-way handshake
34 #pwd:      The password to test
35 #ssid:     the ssid of the ap
36 #A:       b"Pairwise key expansion"
37 #B:       The apMac, cliMac, aNonce, and sNonce concatenated
38 #         like mac1 mac2 nonce1 nonce2
39 #         such that mac1 < mac2 and nonce1 < nonce2
40 #data:     A list of 802.11 frames with the MIC field zeroed
41 #return:   (x, y, z) where x is the mic, y is the PTK, and z is the PTK
42
43 def MakeMIC(pwd, ssid, A, B, data, wpa = False):
44     #Create the pairwise master key using 4096 iterations of hmac sha1
45     #to generate a 32 byte value
46     pmk = pbkdf2_hmac('sha1', pwd.encode('ascii'), ssid.encode('ascii')
47         #Make the pairwise transient key (PTK)
48     ptk = PRF(pmk, A, B)
49     #WPA uses md5 to compute the MIC while WPA2 uses sha1
50     hmacfunc = md5 if wpa else sha1
51     #Create the MICs using HMAC-SHA1 of data and return all computed
52     mics = [hmac.new(ptk[:16], i, hmacfunc).digest() for i in data]
53     return (mics, ptk, pmk)

```


ptk.py outputs PMK, PTK, TK and MIC value



#sf22us

```

95 A,B=FakeMIB(anonce, snonce, aprac, cllmac)
96 mics,ptk,pk,FakePTC(pwd, ssid, A, B, [data1, data2, data3], wpa = False)
97
98 print ("PMK: " + pk.hex())
99 print ("PTK: " + ptk.hex())
100 kek=ptk[0:15]
101 print ("KEK: " + kek.hex())
102 kck=ptk[16:31]
103 print ("KCK: " + kck.hex())
104 tk=ptk[32:48]
105 print ("TK: " + tk.hex())
106 rmic=ptk[48:55]
107 print ("receive MIC secret: " + rmic.hex())
108 tmic=ptk[56:63]
109 print ("transmit MIC Secret: " + tmic.hex())
110
111 mic3str = mics.upper()
112 print("actual mic: " + mic3str)
113 #take the first 128-bits of the 160-bit sha1 hash
114 micStr = b2a_hex(mics[0]).decode().upper()[1:8]
115 print("calculated mic from Message2of4:" + micStr)
116 print('MATCH' if micStr == mic3str else 'MISMATCH')
117 #Display the desired MIC and compare to target MIC2
118 mic2str = mics[1].upper()
119 print("actual mic: " + mic2str)
120 #take the first 128-bits of the 160-bit sha1 hash
121 micStr = b2a_hex(mics[1]).decode().upper()[1:8]
122 print("calculated mic from Message3of4:" + micStr)
123 print('MATCH' if micStr == mic2str else 'MISMATCH')
124 #Display the desired MIC and compare to target MIC3
125 mic3str = mics[2].upper()
126 print("packet mic: " + mic3str)
127 #Take the first 128-bits of the 160-bit sha1 hash
128 micStr = b2a_hex(mics[2]).decode().upper()[1:8]
129 print("packet mic from Message4of4:" + micStr)
130 print('MATCH' if micStr == mic3str else 'MISMATCH')

```

```

PS C:\Users\TakeshitaMegumi\OneDrive - いけりネットワークサービス株式会社\sharkfest
al\Microsoft\WindowsApps\python3.9.exe "c:\Users\TakeshitaMegumi\OneDrive - いけりリ
k.py"
Passphrase:wiresark
SSID:ikeriri6
AP MAC Address from 10f4:f02f74c4f5c4
AP Nonce from 10f4:812e47f04e25fe494c7d44b2f7b016e0ebe3f24865fd234f4998abf5d8d68bc0
STA MAC Address from 10f4:e2da1ea8928f
STA Nonce from 10f4:fcf94398b971a1f28572495509733ff0008c93b142e86c9348ce23f3c287ff8b
PMK: 31bb75a609a24aac01e9929b39458e87ea45b0f30204ff5642bf3067a6fd31f
PTK: 46e515c2a3677ef693f93e8368517684728fe5b36aa9e9fa60e80007a18c05574c102fd43613c535
KEK: 46e515c2a3677ef693f93e83685176
KCK: 728fe5b36aa9e9fa60e80007a18c05
TK: 4c102fd43613c535404d0777088a6503
Receive MIC Secret: 7d9de4d644bb9a
Transmit MIC Secret: de1a23f2e9f17b
actual mic :D5AA6ADF088791D7CD3788866F8A0930
calculated mic from Message2of4:D5AA6ADF088791D7CD3788866F8A0930
MATCH
actual mic :8FC6CCFF6133542E9F8844EC8260E5FF8
calculated mic from Message3of4:8FC6CCFF6133542E9F8844EC8260E5FF8
MATCH
packet mic :E2367DB355CCDF071008D73D06E17585C
packet mic from Message4of4:E2367DB355CCDF071008D73D06E17585C
MATCH
PS C:\Users\TakeshitaMegumi\OneDrive - いけりネットワークサービス株式会社\sharkfest

```

Check the MIC is correct



```

Passphrase: iu!reshark
SSID: ikeri16
AP MAC Address from 10f4:f82f74c4f5c4
AP Nonce from 10f4:812e47f0de25fe494c7d44b2f7b016e0ebe3f24865fd234f4998a0f5d8d68bc0
STA MAC Address from 10f4:e2da1ea8928f
STA Nonce from 10f4:fcf94398b971a1f2d572495509733ff0408c93b142e86c9348ce23f3c287ffab
PRK: 31bb75a609a424aac01e9929b39458e87ea45b0f302d4ff5642bf3067a6fd31f
PTK: 46e515c2a3677ef693f93e8368517684728fe5b36aa9e9fa60e80007a18c85574c102fd43613c535404d0777088a65037d9de4d644bb9a67de1a23f2e9f17b8e
KEK: 46e515c2a3677ef693f93e83685176
KCK: 728fe5b36aa9e9fa60e80007a18c85
TK: 4c102fd43613c535404d0777088a6503
Receive MIC Secret: 7d9de4d644bb9a
Transmit MIC Secret: de1a23f2e9f17b
actual mic: D5AA6ADF008791D7CD37B8866F8A0930
calculated mic from Message2of4:D5AA6ADF008791D7CD37B8866F8A0930
MATCH
actual mic: 8FC6CCF6133542E9F8844EC826DE5FF8
calculated mic from Message3of4:8FC6CCF6133542E9F8844EC826DE5FF8
MATCH
packet mic: E23670B355CCDF071008D73D6E17585C
packet mic from Message4of4:E23670B355CCDF071008D73D6E17585C
MATCH
PS C:\Users\Takeshita\egumi\OneDrive - いけりネットワークサービス株式会社\Sharkfest\Sharkfest2022\03DissectingMPA3>

```

f22us

- The calculated MIC value and packet are the same.
- AP and STA succeeded in sharing the same PTK (and GTK later) without sending key data into the network.

Check TK(Temporal Key)

- TK is used for actual encryption/decryption AES key for unicast data communication between AP and STA.
- Compare the calculated TK from ptk.py with the TK field in CCMP parameters of QoS Data packet (for example, try packet #10) (WPA3-SAE also use this)

```
TK: 4c102fd43613c535404d0777088a6503
```

✓ CCMP parameters

CCMP Ext. Initialization Vector: 00000000000000000000000000000000

Key Index: 0

[TK: 4c102fd43613c535404d0777088a6503]

[PMK: 31bb75a609a424aac01e9929b39458e87ea45b0f30204ff5642bf3067a6fd31f]



BINGO!!

Packet #7 Key(Message 3 of 4) AP->STA

```

40.005013 -33 d..ASUSTekC_c4:f5:c4 e2:da:1e:a8:92:8f Association Response
50.008401 -33 d..ASUSTekC_c4:f5:c4 e2:da:1e:a8:92:8f QoS Data
60.010452 -41 d..e2:da:1e:a8:92:8f ASUSTekC_c4:f5:c4 QoS Data
70.011950 -33 d..ASUSTekC_c4:f5:c4 e2:da:1e:a8:92:8f QoS Data
80.013064 -41 d..e2:da:1e:a8:92:8f ASUSTekC_c4:f5:c4 QoS Data
90.072760 -41 d...: ff02::1:ff01:27fa QoS Data
100.072892 -41 d..e2:da:1e:a8:92:8f ASUSTekC_c4:f5:c5 QoS Data

```

```

Frame 7: 253 bytes on wire (2024 bits), 253 bytes captured (2024 bits) on interface unknown
Radiotap Header v0, Length 32
802.11 radio information
IEEE 802.11 QoS Data, Flags: .....F.
Logical-Link Control
802.1X Authentication
  Version: 802.1X-2004 (2)
  Type: Key (3)
  Length: 183
  Key Descriptor Type: EAPOL RSN Key (2)
  [Message number: 3]
  Key Information: 0x13ca
  Key Length: 16
  Replay Counter: 2
  WPA Key Nonce: 812e47f04e25fe494c7d44b2f7b016e0be3f24865fd234f4998a8f5d8d68bc0
  Key IV: 00000000000000000000000000000000
  WPA Key RSC: 0000000000000000
  WPA Key ID: 0000000000000000
  WPA Key MIC: 8fc6ccf6133542e9f8844ec826de5ff8
  WPA Key Data Length: 88
  WPA Key Data: 8a6607c41f921c7035188bc8a60c1fa1b5a5ae7d0e191e1ce71fa11d8a1a65b302c4c345...

```

- AP creates Nonce (Gnonce), random.
- AP creates and sends GTK safely with KCK / KEK in securely. GTK is used for multicast/broadcast
- AP calculates and adds WPA Key MIC.

GTK creation at AP side

- GTK is created from GMK, Gnonce(Group Nonce), AP's MAC address and Group Key Expansion

GTK 256bits for broadcast / multicast communication

TK(Temporal Key) 128bits AES encryption/decryption key

Receive MIC Key (MIC Secret) 64bits for receiving packet Message Integrity Code

Transmit MIC Key(MIC Secret) 64bits for sending packet Message Integrity Code

- GTK is used for broadcast and multicast, and GTK is the same key between all STA and AP, so GTK will be changed periodically (using a 2-way handshake)

Check the GTK from Message 3of4

- Open WPA Key Data in 802.1X Authentication header of Message 3of4 (Packet #7)
- Open “Tag: Vendor Specific: Ieee 802.11: RSN GTK”

```

v WPA Key Data: 8a6607c41f921c7035108bc8a60c1fa1b5a5ae7d0e191e1ce71fa11d8a1a65b302c4c345...
  > Tag: RSN Information
  v Tag: Vendor Specific: Ieee 802.11: RSN GTK
    Tag Number: Vendor Specific (221)
    Tag length: 22
    OUI: 00:0f:ac (Ieee 802.11)
    Vendor Specific OUI Type: 1
    .... ..01 = KeyID: 1
    .... .0.. = Tx: 0
    0000 0... = Reserved: 0x00
    Reserved: 0
    GTK: eeda95a1155a28f86c030d000c1fdd9a
  > Tag: Vendor Specific: Ieee 802.11: RSN IGTK
    WPA Key Data Padding: dd000000
    [KCK: 46e515c2a3677ef693f93e8368517684]
    [KEK: 728fe5b36aa9e9fa60e80007a18c0557]
```



Compare KCK and KEK

- KCK(Key Confirmation Key) and KEK(Key Encryption Key) are used for secure key distribution.
- Confirm Wireshark calculated KCK, KEK is the same with ptk.py generated KCK, KEK

```
GTK: eeda95a1155a28f86c030d000c1fdd9a
```

```
> Tag: Vendor Specific: Ieee 802.11: RSN IGTK
```

```
WPA Key Data Padding: dd000000
```

```
[KCK: 46e515c2a3677ef693f93e8368517684]
```

```
[KEK: 728fe5b36aa9e9fa60e80007a18c0557]
```

```
KEK: 46e515c2a3677ef693f93e8368517684
```

```
KCK: 728fe5b36aa9e9fa60e80007a18c0557
```

- It means GTK sends/receives securely

Packet #7 Key(Message 4of4) STA->AP

```


4 0.005013 -33 d..ASUSTekC_c4:f5:c4 e2:da:1e:a8:92:8f Association Respo
5 0.008401 -33 d..ASUSTekC_c4:f5:c4 e2:da:1e:a8:92:8f QoS Data
6 0.010452 -41 d...e2:da:1e:a8:92:8f ASUSTekC_c4:f5:c4 QoS Data
7 0.011950 -33 d..ASUSTekC_c4:f5:c4 e2:da:1e:a8:92:8f QoS Data
8 0.013064 -41 d...e2:da:1e:a8:92:8f ASUSTekC_c4:f5:c4 QoS Data
9 0.072760 -41 d...: ff02::1:ff01:27fa QoS Data
10 0.072892 -41 d...e2:da:1e:a8:92:8f ASUSTekC_c4:f5:c5 QoS Data
11 0.073031 -41 d...0.0.0.0 255.255.255.255 QoS Data
12 0.073376 -41 d...fe80::1c42:c607:... ff02::2 QoS Data
13 0.073578 -33 d...: ff02::1:ff01:27fa Data

Frame 8: 165 bytes on wire (1320 bits), 165 bytes captured (1320 bits) on interface
Radiotap Header v0, Length 32
802.11 radio information
IEEE 802.11 QoS Data, Flags: .....T
Logical-Link Control
802.1X Authentication
  Version: 802.1X-2004 (2)
  Type: Key (3)
  Length: 95
  Key Descriptor Type: EAPOL RSN Key (2)
  [Message number: 4]
  Key Information: 0x030a
  Key Length: 16
  Replay Counter: 2
  WPA Key Nonce: 0000000000000000000000000000000000000000000000000000000000000000
  Key IV: 0000000000000000000000000000000000000000000000000000000000000000
  WPA Key RSC: 0000000000000000
  WPA Key TD: 0000000000000000
  WPA Key MIC: e2367db355ccdf0710d8d73d6e175b5c
  WPA Key Data Length: 0

```

- STA received and installed GTK in Message 3of4 (#6)
- STA adds WPA Key MIC for confirmation
- AP receives Message 4of4 and confirms packet MIC with calculated MIC.

Conclusion: 4 way handshake in WPA2/WPA3



```

Passphrase:wineshark
SSID:ikerir16
AP MAC Address from 10f4:1f2f:74c4:f5c4
AP Nonce from 10f4:1812e47f04e25f0494c7d44b2f7b018e0e0e3f24885fd234f4998a8f508d680c0
STA MAC Address from 10f4:e2da1eaa8928f
STA Nonce from 10f4:fcf94398b971a1f20572495509733ff0000c93b142e06c9348ce23f3c287ff0b
PRK: 31bb75a009a424aac01e9929b39458e87ea45b0f30204ff5642bf3067a6fd31f
PTK: 46e515c2a3677ef693f93e8368517684728fe5b36aa9e9fa60e08007a18c05574c102fd43613c535404d8777888a65037d9de4d544bb9a67de1a23f2e9f17b8e
KEK: 46e515c2a3677ef693f93e8368517684
ECK: 728fe5b36aa9e9fa60e08007a18c0557
TK: 4c102fd43613c535404d07778008a6503
Receive MIC Secret: 709de8d644bbsa
Transmit MIC Secret: de1a23f2e9f17b
actual mic:D5AA6ADF08879107CD37B8866F8A0930
calculated mic from Message2of4:D5AA6ADF00B79107CD37B8866F8A0930
WATCH
actual mic:8FC6CCF6133542E9F8B44EC826DE5FF8
calculated mic from Message3of4:8FC6CCF6133542E9F8B44EC826DE5FF8
WATCH
packet mic:E236708355CDF071000D73D6E175B5C
packet mic from Message4of4:E236708355CDF071000D73D6E175B5C
WATCH
  
```

WPA2 is good, but...

- It has been over ten years since WPA2 was born.
- We can use a dictionary attack if we capture a complete 4-way handshake between AP and STA.
- Smartphones and tablets are positive to roam, so faked Deauthentication and Disassociation frames can lead to tons of new 4-way handshake packets.
- Some new attack method comes, for example, KRACKS blocks the original Message3of4 from AP and tries many GTK patterns to assure keys.

Deauth attack

- faked Deauthentication and Disassociation frames can lead to tons of fresh 4-way handshake packet
airreplay-ng --deauth wlan0mon
- Use dictionary attack if we capture just a set of a complete 4-way handshake between AP and STA.
- Open deauthattack.pcap and set Display filter as “wlan.fc.type_subtype==12 or eapol”
- You can find many 4-way handshake packets of Stations (Sony_xx:yy:zz) after Deauthentication.

Open deauthattack.pcap



#sf22us

No.	Time	Signal (dBm)	Source	Destination	Type/Subtype	Data	Protocol	Length	Info
442	358.904..	-58	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	45	Deauthentication, SN=219	
442	358.912..	-58	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
442	358.914..	-57	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
442	358.921..	-58	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.850..	-60	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.109..	-62	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.113..	-62	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.120..	-62	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.124..	-62	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.149..	-63	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.163..	-62	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.174..	-61	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
443	359.177..	-60	dBm PlanexCo_e3:c2:79	Sony_50:73:db	Deauth...	1 802.11	50	Deauthentication, SN=219	
252	262.858..	-58	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Deauth...	1 802.11	50	Deauthentication, SN=217	
252	262.374..	-60	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	177	Key (Message 1 of 4)	
252	262.450..	-60	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	211	Key (Message 3 of 4)	
313	293.295..	-63	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	177	Key (Message 1 of 4)	
313	293.299..	-63	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	177	Key (Message 1 of 4)	
313	293.571..	-64	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	177	Key (Message 1 of 4)	
313	293.580..	-64	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	177	Key (Message 1 of 4)	
313	293.587..	-63	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	177	Key (Message 1 of 4)	
313	293.592..	-64	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	177	Key (Message 1 of 4)	
314	293.644..	-62	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	89	Key [Malformed Packet]	
314	293.685..	-61	dBm PlanexCo_e3:c2:79	Sony_53:d6:0a	Data	1 EAPOL	177	Key (Message 1 of 4)	

- faked Deauthentication frames (source address is faked AP) lead to tons of fresh 4-way handshake

WPA3 Wi-Fi Protected Access

- WPA3 is the new security standard for wireless networks.
https://www.wi-fi.org/download.php?file=/sites/default/files/private/WPA3_Specification_v3.0.pdf
- WPA3 personal mode (WPA3-SAE) uses SAE (Simultaneous Authentication of Equals), derived from Dragonfly Key Exchange (RFC7664), instead of open authentication.
<https://www.rfc-editor.org/info/rfc7664>
- AP and STA exchange 4 packets (AP/STA Commit, AP/STA Confirm) and create PMK at the authentication phase, So PMK is different every time. This provides forward security, we cannot attack from an old 4-way handshake with the fresh PMK. (WPA2-PSK uses the same PMK) It means a dictionary attack is (almost) impossible!!

#sf22us

- Compare wpa2psk-ssid-ikeriri6-pass-wireshark.pcapng with wpa3psk-ssid-ikeriri6-pass-wireshark.pcapng
- Both WPA2 and WPA3 use the same 4-way handshake mechanism to create and share PTK, GTK



#sf22us

No.	Time	Signal Label	Source	Destination	Type/Protocol	Data Protocol	Length	Info
18.000000	-39	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	Authentication	6802.11	97	Authentication, SN=833, FN=0, Flags=.....	
28.001283	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	Authentication	6802.11	62	Authentication, SN=0, FN=0, Flags=.....	
38.002746	-41	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	Association Request	6802.11	237	Association Request, SN=834, FN=0, Flags=.....	
48.005813	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	Association Response	6802.11	318	Association Response, SN=1, FN=0, Flags=.....	
58.008401	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	QoS Data	6EAPOL	165	Key (Message 1 of 4)	
68.010493	-41	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	QoS Data	6EAPOL	187	Key (Message 2 of 4)	
78.011956	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	QoS Data	6EAPOL	253	Key (Message 3 of 4)	
88.013664	-41	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	QoS Data	6EAPOL	165	Key (Message 4 of 4)	
98.072708	-41	d8n ::	ff02::1:ff01:27fa	QoS Data	ICMPv6	178	Neighbor Solicitation for fe80::1c42:c607:6801:27fa	
108.072893	-41	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C5	QoS Data	ARP	136	who has 192.168.50.1? Tell 192.168.50.236	
118.073831	-41	d8n 0.0.0.0	255.255.255.255	QoS Data	DHCP	426	DHCP Request - Transaction ID 0xac9e7580	
128.073376	-41	d8n fe80::1c42:c607::	ff02::2	QoS Data	ICMPv6	148	Router Solicitation	
138.073578	-31	d8n ::	ff02::1:ff01:27fa	Data	ICMPv6	136	Neighbor Solicitation for fe80::1c42:c607:6801:27fa	

WPA2



WPA3

No.	Time	Signal Label	Source	Destination	Type/Protocol	Data Protocol	Length	Info
18.000000	-36	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	Authentication	6802.11	160	Authentication, SN=3841, FN=0, Flags=.....	
28.028660	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	Authentication	6802.11	160	Authentication, SN=0, FN=0, Flags=.....	
38.095378	-38	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	Authentication	6802.11	96	Authentication, SN=3802, FN=0, Flags=.....	
48.059667	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	Authentication	6802.11	96	Authentication, SN=1, FN=0, Flags=.....	
58.062471	-38	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	Association Request	6802.11	255	Association Request, SN=3845, FN=0, Flags=.....	
68.064576	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	Association Response	6802.11	293	Association Response, SN=1, FN=0, Flags=.....	
78.067697	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	QoS Data	6EAPOL	187	Key (Message 1 of 4)	
88.070141	-58	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	QoS Data	6EAPOL	205	Key (Message 2 of 4)	
98.071868	-31	d8n ASUSTek_C4:F5:C4	e2:da:1e:a8:92:8f	QoS Data	6EAPOL	253	Key (Message 3 of 4)	
108.073831	-38	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	QoS Data	6EAPOL	165	Key (Message 4 of 4)	
118.075896	-40	d8n e2:da:1e:a8:92:8f	ASUSTek_C4:F5:C4	QoS Data	...	74	QoS Null function (No data), SN=3844, FN=0	
128.421881	-40	d8n e2:da:1e:a8:92:8f	IP6multicast_ff:01::	QoS Data	...	170	QoS Data, SN=0, FN=0, Flags=op.....T	
138.421885	-60	d8n e2:da:1e:a8:92:8f	Broadcast	QoS Data	...	426	QoS Data, SN=1, FN=0, Flags=op.....T	

Difference between WPA2 and WPA3

Explanation	WPA2 Personal WPA2-PSK	WPA3 Personal WPA3-SAE
PTK, GTK exchange	Both WPA2 and WPA3 use 4 way handshake	
Passphrase length	From 8 to 63 characters	From 8 to 128 characters
Temporal Key (encryption key)	AES(128bits)	AES(128bits)
Authentication method (PMK creation)	Open System/Shared key authentication PSK+SSID->PMK	SAE (Simultaneous Authentication of Equals)
Encryption of Management frame	Not nessary	PMF (Protected Management Frames) (Optionally)
Brute force prevention	Not nessary	Lock out a device after a number of unsuccessful attempts (Optionally)

- Open wpa2 trace file and set display filter as “wlan.fc.type_subtype == 0x000b”
- Extract IEEE802.11 Wireless Management

```

> Frame 1: 97 bytes on wire (776 bits), 97 byte
> Radiotap Header v0, Length 32
> 802.11 radio information
> IEEE 802.11 Authentication, Flags: .....
v IEEE 802.11 Wireless Management
  v Fixed parameters (6 bytes)
    Authentication Algorithm: Open System (0)
    Authentication SEQ: 0x0001
    Status code: Successful (0x0000)
  > Tagged parameters (35 bytes)

```

```

> Frame 2: 62 bytes on wire (496 bits), 62 byte
> Radiotap Header v0, Length 32
> 802.11 radio information
> IEEE 802.11 Authentication, Flags: .....
v IEEE 802.11 Wireless Management
  v Fixed parameters (6 bytes)
    Authentication Algorithm: Open System (0)
    Authentication SEQ: 0x0002
    Status code: Successful (0x0000)

```

- WPA2 Open System Authentication checks the match of SSID name (ikeriri6)

- Open wpa3 trace file and set display filter as “wlan.fc.type_subtype == 0x000b”
- Extract IEEE802.11 Wireless Management
- There are 4 Authentication packets with SAE Message type as follows STA Commit(1), AP Commit(1), STA Confirm(2), AP Confirm(2)

✓ IEEE 802.11 Wireless Management

✓ Fixed parameters (104 bytes)

Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3)

Authentication SEQ: 0x0001

Status code: Successful (0x0000)

SAE Message Type: Commit (1)

Group Id: 256-bit random ECP group (19)

Scalar: c67801ac5941d1e0fad412b255567e53c885a0d12a22439a3e021c7d633f37e7

Finite Field Element: f4b7c34e9f0d5444381e1dde353e54dcc838435b372a3933b7cc

Understand Dragonfly key exchange with simple example



- Dragonfly use Elliptic-Curve Cryptography(ECC)
ECC is a difficult mathematical theory, so think this in programming words easily.
- The finite field is a mathematical term, in other words, the calculatable mod value collection.
if we set mod value $p=11$ (p :prime field $GF(p)$)
and the mod collection is $\{0, 1, 2, \dots, 9, 10\}$
we can calculate the mod collection, for example
 $3 * 5 = 15$ is a element of the mod collection
 $3*5=15 \equiv 4 \pmod{11}$. We use this for Elliptic-Curve Discrete Logarithm Problem (seems difficult...)

Understand Dragonfly key exchange with simple example

- We can translate Elliptic-Curve Discrete Logarithm Problem in a computer program like below,
int a=2,n=5,p=11, b=a^n mod p (^:exponentiation)
we can calculate b easily from a,n,p
$$b=2*2*2*2*2 \text{ mod } 11=32 \text{ mod } 11 =10$$
- So how do we find n (Logarithm) from a,b and p,
we need to test incrementally, n=1, n=2, n=3, ...
if the parameters are such a vast number, finding Logarithm n is almost impossible in today's PC
- ECC use this ECDLP for encryption

Understand Dragonfly key exchange with simple example


- We can translate the Elliptic-Curve Discrete Logarithm Problem in a computer program like,
int a=2,n=5,p=11, b=a^n mod p (^:exponentiation)
we can calculate b easily from a,n,p
 $b=2*2*2*2*2 \text{ mod } 11=32 \text{ mod } 11 =10$
- So how do we find n (Logarithm) from a,b and p,
we need to test incrementally, n=1, n=2, n=3, ...
if the parameters are such a vast number, finding
Logarithm n is almost impossible to calculate.
- ECC use this ECDLP for encryption.

Dragonfly handshake of WPA3-PSK



#sf22us

○ Create Statistics>Flow Graph



- Both AP and STA can initiate the handshake, send Auth-Commit and Auth-Confirm each other with scholar and (finite field) element value.

```

- IEEE 802.11 Wireless Management
  - Fixed parameters (104 bytes)
    Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3)
    Authentication SEQ: 0x0001
    Status code: Successful (0x0000)
    SAE Message Type: Commit (1)
    Group Id: 256-bit random ECP group (19)
    Scalar: c67801ac5941d1e0fad412b255567e53c885a0d12a22439a3e021c7d633f37e7
    Finite Field Element: f4b7c34e9f0d5444381e1dde353e54dcc838435b372a3933b7ccc

- IEEE 802.11 Wireless Management
  - Fixed parameters (104 bytes)
    Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3)
    Authentication SEQ: 0x0001
    Status code: Successful (0x0000)
    SAE Message Type: Commit (1)
    Group Id: 256-bit random ECP group (19)
    Scalar: 3fed4910393e5fa8fa5ac12ab8fa9bdfcf8094ded96acfa887620f801c0ee564
    Finite Field Element: 94a0809ac7b9759a54dc8a9e408e7566f053d79673f2f5a650ed

- IEEE 802.11 Wireless Management
  - Fixed parameters (40 bytes)
    Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3)
    Authentication SEQ: 0x0002
    Status code: Successful (0x0000)
    SAE Message Type: Confirm (2)
    Send-Confirm: 1
    Confirm: a05a007d7ffce2004a95d7d7d32296c5b8ffa87e5777d2dfa3f7a8e76fce2343

- IEEE 802.11 Wireless Management
  - Fixed parameters (40 bytes)
    Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3)
    Authentication SEQ: 0x0002
    Status code: Successful (0x0000)
    SAE Message Type: Confirm (2)
    Send-Confirm: 0
    Confirm: 6dc3f845c7772c6fa7ec01b95802b850ceb848e9dd13019c6513c3311c05cc4f
  
```

- SAE handshake has 2 Auth-Commit and 2 Auth-Confirm messages
- Auth-Commit has Scalar(sA,sB) and Finite Field Element (eA,eB)
- Auth-Confirm has a Confirm value
- They create and share PMK during these 4 packets

#1: Auth-Commit from Alice(STA)

```

v IEEE 802.11 Wireless Management
  v Fixed parameters (104 bytes)
    Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3)
    Authentication SEQ: 0x0001
    Status code: Successful (0x0000)
    SAE Message Type: Commit (1)
    Group Id: 256-bit random ECP group (19)
    Scalar: c67801ac5941d1e0fad412b255567e53c885a0d12a22439a3e021c7d633f37e7
    Finite Field Element: f4b7c34e9f0d5444381e1dde353e54dcc838435b372a3933b7cc
  
```

- Alice(STA) picks random r_A and m_A and calculates $s_A = (r_A + m_A) \bmod q$
- $e_A = -m_A \cdot GF(p)$ (\cdot means inner products of vector)
- Then send Auth-Commit with s_A (256bits Scalar) and $GF(p)$ (512bits Finite Field Element)

#2: Auth-Commit from Bob(AP) at same time



```

v IEEE 802.11 Wireless Management
  v Fixed parameters (104 bytes)
    Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3)
    Authentication SEQ: 0x0001
    Status code: Successful (0x0000)
    SAE Message Type: Commit (1)
    Group Id: 256-bit random ECP group (19)
    Scalar: 3fed4910393e5fa8fa5ac12ab8fa9bdfcf8094ded96acfa887620f801c0ee564
    Finite Field Element: 94a0809ac7b9759a54dc8a9e408e7566f053d79673f2f5a650ed
  
```

- Bob(AP) picks random r_B and m_B and calculates $s_B = (r_B + m_B) \bmod q$
- $e_B = -m_B \cdot GF(p)$ (\cdot means inner products of vector)
- Then send Auth-Commit with s_B (256bits Scalar) and $GF(p)$ (512bits Finite Field Element)

Auth-Commit (Scalar, Finite Field Element)



#sf22us

Random: a, A

$$sA = (a+A) \bmod q$$

$$\text{element}A = PE^{-A}$$

Random: b, B

$$sB = (b+B) \bmod q$$

$$\text{element}B = PE^{-B}$$

 sA, PE^{-A}
 sB, PE^{-B}

$$\begin{aligned} ss &= (PE^{sB} \times PE^{-B})^a \\ &= (PE^{b+B-B})^a \\ &= PE^{ab} \end{aligned}$$

$$\begin{aligned} ss &= (PE^{sA} \times PE^{-A})^b \\ &= (PE^{a+A-A})^b \\ &= PE^{ab} \end{aligned}$$

- Each Alice(STA) and Bob(AP) calculate their own and the other side Scalar and Finite field element to create and share PE(Password Equivalent) value.

3.2.1. Hunting and Pecking with ECC

- Each Alice(STA) and Bob(AP) determine random values and $GF(p)$ Finite Field Element, but How? ^{#sf22us}
- RFC7664 Dragonfly key exchange defines a “Hunting and Pecking” algorithm to determine PE(Password Equivalent), try to find the point in the Elliptic Curve from Alice(STA) and Bob(AP) MAC addresses.
<https://www.rfc-editor.org/info/rfc7664>
- We need over 40 times iterations of hunting and pecking loop against side-channel attack.
(first implementation of Dragonfly)

3.2.1. Hunting and Pecking with ECC

- We calculate the base value, the hash from the counter, mac addresses of Alice and Bob and the passphrase (counter=1)^{#sf22us}
base = $H(\max(\text{Alice}, \text{Bob}) \mid \min(\text{Alice}, \text{Bob}) \mid \text{password} \mid \text{counter})$
- We use KDF(key derivation function) to create bitstream temp value(length is prime number) and the seed
 $n = \text{len}(p) + 64$
temp = KDF-n (base, "Dragonfly Hunting and Pecking")
seed = $(\text{temp} \bmod (p - 1)) + 1$
- Start loop to find the valid point of Elliptic Curve, use seed as x-axis parameter to check $x^3 + a*x + b$ is a quadratic residue modulo p. if not, the counter increase, create new seed and set x-axis, current base value.

Hunting and Pecking with ECC Groups 3.2.1 RFC7664



#sf22us

```

found = 0
  counter = 1
  n = len(p) + 64
  do {
    base = H(max(Alice,Bob) | min(Alice,Bob) | password |
counter)
    temp = KDF-n(base, "Dragonfly Hunting And Pecking")
    seed = (temp mod (p - 1)) + 1
    if ( (seed^3 + a*seed + b) is a quadratic residue mod p)
    then
      if ( found == 0 )
      then
        x = seed
        save = base
        found = 1
      fi
    fi
    counter = counter + 1
  } while ((found == 0) || (counter <= k))
  y = sqrt(x^3 + ax + b)
  if ( lsb(y) == lsb(save) )
  then
    PE = (x,y)
  else
    PE = (x,p-y)
  fi

```

#3: Auth-Confirm from Alice(STA)



```

v IEEE 802.11 Wireless Management
  v Fixed parameters (40 bytes)
    Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3) 22us
    Authentication SEQ: 0x0002
    Status code: Successful (0x0000)
    SAE Message Type: Confirm (2)
    Send-Confirm: 1
    Confirm: e05e00747ffce2d04a55d7d7d32296c5b8ffa07e5777d2dfa3f7a8e74fce2343
  
```

- Alice(STA) verifies s_B and e_B , calculates $K = r_A \cdot (s_B \cdot P + e_B)$ (\cdot means inner products)
- $tr = (s_A, e_A, s_B, e_B)$ (Alice and Bob know these values)
- $c_A = \text{HMAC}(\text{Hash}(K), tr)$
- Then send Auth-Confirm with c_A (256bits Confirm)

#4: Auth-Confirm from Bob(AP)



```

v IEEE 802.11 Wireless Management
  v Fixed parameters (40 bytes)
    Authentication Algorithm: Simultaneous Authentication of Equals (SAE) (3)
    Authentication SEQ: 0x0002
    Status code: Successful (0x0000)
    SAE Message Type: Confirm (2)
    Send-Confirm: 0
    Confirm: 6dc3f845c7772c6fa7ec01b95802b850ceb840e9dd13019c6515c3311c05cc4f
  
```

- Bob(AP) verifies s_A and e_A , calculates $K = r_B \cdot (s_A \cdot P + e_A)$ (\cdot means inner products)
- $tr = (s_B, e_B, s_A, e_A)$ (Alice and Bob know these values)
- $c_B = \text{HMAC}(\text{Hash}(K), tr)$
- Then send Auth-Confirm with c_B (256bits Confirm)

Auth-Confirm (Confirm value)

Confirm-A = Hash(KCK | scalarA | a |
elementA | elementB)

Confirm-B = Hash(KCK | scalarB | b,
elementB | elementA)



#sf22us

- Each Alice(STA) and Bob(AP) can verify the packet's Confirm value with the calculated Confirm value
- $K=rB \cdot (sA \cdot P + eA)$ • $K=rA \cdot (sB \cdot P + eB)$
 $tr=(sB, eB, sA, eA)$ $tr=(sA, eA, sB, eB)$
 $cB=HMAC(Hash(K), tr)$ $cA=HMAC(Hash(K), tr)$
- If the calculated Confirm value is the same as the packet, we can share PE(Password Equivalent) value without sending passphrase information to each other.

PMK creation from PE value



#sf22us

- ⦿ Then Alice(STA) and Bob(AP) create PMK from PE(Password Equivalent) value.
- ⦿ Random values make PE, so PMK is different every time during Dragonfly key exchange
- ⦿ Let's check this, dragonfly_implementation.py is the sample Python code for the Dragonfly (SAE) handshake implementation by NikolaiT.
https://github.com/NikolaiT/Dragonfly-SAE/blob/master/dragonfly_implementation.py
- ⦿ Open dragonfly_implementation.py in VSCode

Check Commit Values



#sf22us

```

2022-07-01 23:26:10,663 dragonfly DE0 [STA] Sending scalar and element to the peer
2022-07-01 23:26:10,663 dragonfly DE0 [STA] Scalar=376657120602076341288635327581518817518660388641217718708210767161128574819
2022-07-01 23:26:10,663 dragonfly DE0 [STA] Element=FiniteFieldElement(376657120602076341288635327581518817518660388641217718708210767161128574819, y=21588016015068371145359265382911661365371091386688352851210096807952682560)
2022-07-01 23:26:10,760 dragonfly DE0 [AP] Sending scalar and element to the peer
2022-07-01 23:26:10,760 dragonfly DE0 [AP] Scalar=30769516020180780275417386507656548486782788715707522813410121022916721879211
2022-07-01 23:26:10,760 dragonfly DE0 [AP] Element=FiniteFieldElement(30769516020180780275417386507656548486782788715707522813410121022916721879211, y=21588016015068371145359265382911661365371091386688352851210096807952682560)
2022-07-01 23:26:10,750 dragonfly DE0 Comparing shared secret...
2022-07-01 23:26:10,750 dragonfly DE0 [STA] Shared Secret=3566687402926688938225177802188995314585788015726401238810788015273176497801166
2022-07-01 23:26:10,800 dragonfly DE0 [AP] Shared Secret=3566687402926688938225177802188995314585788015726401238810788015273176497801166
2022-07-01 23:26:10,800 dragonfly DE0 Confirm Exchange...
2022-07-01 23:26:10,800 dragonfly DE0 [STA] Received Token from Peer=SharedElement(34228862171429764d7d4d94d27b70f18e1f1bc51c7d
2022-07-01 23:26:10,800 dragonfly DE0 [STA] Received Token from Peer=SharedElement(34228862171429764d7d4d94d27b70f18e1f1bc51c7d
2022-07-01 23:26:10,800 dragonfly DE0 [STA] Received Token from Peer=SharedElement(34228862171429764d7d4d94d27b70f18e1f1bc51c7d
2022-07-01 23:26:10,800 dragonfly DE0 [AP] Received Token from Peer=SharedElement(34228862171429764d7d4d94d27b70f18e1f1bc51c7d
2022-07-01 23:26:10,800 dragonfly DE0 [AP] Received Token from Peer=SharedElement(34228862171429764d7d4d94d27b70f18e1f1bc51c7d
2022-07-01 23:26:10,800 dragonfly DE0 [AP] Received Token from Peer=SharedElement(34228862171429764d7d4d94d27b70f18e1f1bc51c7d
2022-07-01 23:26:10,800 dragonfly DE0 [AP] Received Token from Peer=SharedElement(34228862171429764d7d4d94d27b70f18e1f1bc51c7d

```

- ⦿ Please check Commit Value
 - [STA] Scalar and [STA] Element (Finite Field Element)
 - [AP] Scalar and [AP] Element (Finite Field Element)
- ⦿ Please check Confirm Value
 - [STA] Received Token from Peer
 - [AP] Received Token from Peer

Check Confirm value

```

2022-07-03 23:34:02,968 - dragonfly - INFO - Confirm Exchange...
2022-07-03 23:34:02,968 - dragonfly - INFO - [STA] Computed Token from Peer=13e297cb9a9dcea5d33be06237fa2878dadf4d994287bf0f1de343bcbae51cfd
2022-07-03 23:34:02,968 - dragonfly - INFO - [STA] Received Token from Peer=13e297cb9a9dcea5d33be06237fa2878dadf4d994287bf0f1de343bcbae51cfd
2022-07-03 23:34:02,968 - dragonfly - INFO - [STA] Pairwise Master Key(PMK)=e0c89767cd00f2f6193bb9439a7df0f7e37a853ff4e6e612b84b4967ca0849b9
2022-07-03 23:34:02,969 - dragonfly - INFO - [AP] Computed Token from Peer=c16f119f89b4b0e39b3450c0466baacacaa1824b8a0ab2dd1fb46fb33bef4c8
2022-07-03 23:34:02,969 - dragonfly - INFO - [AP] Received Token from Peer=c16f119f89b4b0e39b3450c0466baacacaa1824b8a0ab2dd1fb46fb33bef4c8
2022-07-03 23:34:02,969 - dragonfly - INFO - [AP] Pairwise Master Key(PMK)=e0c89767cd00f2f6193bb9439a7df0f7e37a853ff4e6e612b84b4967ca0849b9
PS C:\Users\takeshitameguri\OneDrive - いけり ネットワークサービス株式会社\sharkfest\sharkfest2022\03DissectingMPA1>
  
```

Also, check Packet's Confirm Value is the same with calculated Confirm Value

[STA] Computed Token from Peer is the same with

[STA] Received Token from Peer

[AP] Computed Token from Peer is the same with

[AP] Received Token from Peer

Check shared secret(PE), PMK



#sf22us

- Look for each shared secret(Password Equivalent) value between Alice(STA) and Bob(AP).
[STA] Shared Secret and [AP] Shared Secret
- Also, check PMK values, [STA] Pairwise Master Key(PMK) and [AP] Pairwise Master Key(PMK)
Yes, we can share PE, PMK sending passphrase information to each other.
- Let's try over 2 times. You can find these values are different at every try.

PMK, shared key is different!!



1st try

```

2022-07-03 23:34:02,858 - dragonfly - INFO - [STA] Shared Secret ss=69807381029888038225177021188985319505788035726401238610784021527476407801166
2022-07-03 23:34:02,968 - dragonfly - INFO - [AP] Shared Secret ss=69807381929808938225177021188985319505788035726401238610784021527476497801166

2022-07-03 23:34:02,968 - dragonfly - INFO - Confirm Exchange...

2022-07-03 23:34:02,968 - dragonfly - INFO - [STA] Computed Token from Peer=13e297cb9a9dcea5d33be06237fa2878dadfd4d994287bf0f1de343bcbac51cfd
2022-07-03 23:34:02,968 - dragonfly - INFO - [STA] Received Token from Peer=13e297cb9a9dcea5d33be06237fa2878dadfd4d994287bf0f1de343bcbac51cfd
2022-07-03 23:34:02,968 - dragonfly - INFO - [STA] Pairwise Master Key(PMK)=e0c89767cd0bf2f6193bb9439a7d0f7e37a853ff4e6e612b84b4967ca0849b9
2022-07-03 23:34:02,969 - dragonfly - INFO - [AP] Computed Token from Peer=c16f119f89b4b0e39b3450c0466baacacaa1824b8a0ab2dd11b4611b33bef4c8
2022-07-03 23:34:02,969 - dragonfly - INFO - [AP] Received Token from Peer=c16f119f89b4b0e39b3450c0466baacacaa1824b8a0ab2dd11b4611b33bef4c8
2022-07-03 23:34:02,969 - dragonfly - INFO - [AP] Pairwise Master Key(PMK)=e0c89767cd0bf2f6193bb9439a7d0f7e37a853ff4e6e612b84b4967ca0849b9
PS C:\Users\takeshita\egumi\OneDrive - いけり ネットワークサービス株式会社\Sharkfest\Sharkfest2022\03Dissecting\MPA3>

```



2nd try

```


2022-07-03 23:51:33,556 - dragonfly - INFO - [STA] Shared Secret ss=1189115326235807803685727071259681376814918900581134690318478988316425160022
2022-07-03 23:51:33,665 - dragonfly - INFO - [AP] Shared Secret ss=1189115326235807803685727071259681376814918900581134690318478988316425160022

2022-07-03 23:51:33,666 - dragonfly - INFO - Confirm Exchange...

2022-07-03 23:51:33,666 - dragonfly - INFO - [STA] Computed Token from Peer=ae98151668650840769ccabb0951d16ddbabb736f4d6500272b0ec7c12d64fbf
2022-07-03 23:51:33,666 - dragonfly - INFO - [STA] Received Token from Peer=ae98151668650840769ccabb0951d16ddbabb736f4d6500272b0ec7c12d64fbf
2022-07-03 23:51:33,667 - dragonfly - INFO - [STA] Pairwise Master Key(PMK)=d29fb108095ad3ec6b0cf4da267eaad8605c6b45ef7a5dbf5d5632689e4190f0
2022-07-03 23:51:33,667 - dragonfly - INFO - [AP] Computed Token from Peer=e6d936182c952456c74cc26b05636965c531d0f1d71ed4dfc9a2759f70fe31d7
2022-07-03 23:51:33,667 - dragonfly - INFO - [AP] Received Token from Peer=e6d936182c952456c74cc26b05636965c531d0f1d71ed4dfc9a2759f70fe31d7
2022-07-03 23:51:33,667 - dragonfly - INFO - [AP] Pairwise Master Key(PMK)=d29fb108095ad3ec6b0cf4da267eaad8605c6b45ef7a5dbf5d5632689e4190f0
PS C:\Users\takeshita\egumi\OneDrive - いけり ネットワークサービス株式会社\Sharkfest\Sharkfest2022\03Dissecting\MPA3>

```

Forward Security, PMF and lockout



- We understand PMK is different every time in WPA3, it provides Forward Security.
- We cannot use a offline dictionary attack
- Deauth attack is impossible with PMF (Protected Management Frames). (optionally)
- Wrong passphrase lockout function prevents brute force attack. (optionally)
- WPA3-SAE is (almost) impossible for cracking now.

Vulnerabilities of WPA3 dragon blood



#sf22us

- Downgrade WPA3-SAE to WPA2-PSK
- DoS attack with over 70 connection requests (Hunting and Pecking calculation DoS) may stop AP.
- Hunting and Pecking use 40 round time to find random values, so the old implementation may be weak with a side-channel attack.
- Chosen random value attack: set rB to zero.
- Enable Brute force using a faked mac address to avoid lockout, and so on...

-> these vulnerabilities are (almost) fixed now!!

Appendix: WPA3-EAP



#sf22us

- WPA3 Enterprise mode is called WPA3-EAP
- WPA3-EAP use CSNA (Commercial National Security Algorithm) 192bit encryption instead of AES.
- WPA3 needs a RADIUS (802.1x authentication) server
We can use TLS, LEAP, PEAP and other authentication methods, the authentication server provides each connection's PMK.
- WPA3-EAP is the best choice if your network has many users and APs. (if your company has a budget)

USE WIRESHARK



Thank you for watching !!

#sf22us

Please complete app-based survey



trace files and python codes are here:

<https://www.ikeriri.ne.jp/sharkfest/03DissectingWPA3.zip>



ikeriri network service

<http://www.ikeriri.ne.jp>